

Power Inductor AWT Series

**Automotive
AEC-Q200**

RoHS Compliant
Halogen Free
REACH Compliant




- Power Circuit
- Shield
- Magnetic Resin LVx
- Ferrite
- High Current

Part Numbering

A	WVT	00	252012	1R0	M	00
Grade	Series Name	Control Code	Dimensions Code (mm)	Inductance (uH)	Tolerance	Internal Code
			201610 2.0x1.6x1.0	R47 0.47	M ±20%	
			252010 2.5x2.0x1.02	1R0 1.0	T ±30%	
			252012 2.5x2.0x1.2	101 100		
			303010 3.0x3.0x1.02			
			303012 3.0x3.0x1.2			
			404012 4.0x4.0x1.2			
			404015 4.0x4.0x1.5			
			404026 4.0x4.0x2.6			
			505020 5.0x5.0x2.0			
			606020 6.0x6.0x2.0			
			808040 8.0x8.0x4.0			


AWVT00201610 Type

■ Dimensions



unit:mm

■ Recommended Land Pattern



unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT00201610R47□00	0.47	1MHz,200mV	0.072	2.40(2.10)	2.40(2.10)	20,30	A

Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

1. Operating temperature range -40°C ~ 125°C (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current.
3. I rms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:

L: HP4285A+HP42841A

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent


Isat: Agilent HP4284A

I rms: Agilent HP4284A


AWVT00201610 Type

■ Characteristics Graph


Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

AWVT00252010 Type
■ Dimensions


unit:mm

■ Recommended Land Pattern


unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT00252010R68□00	0.68	1MHz,200mV	0.050	2.40(2.10)	2.20(1.90)	20,30	K
AWVT002520102R2□00	2.2	1MHz,200mV	0.135	1.40(1.20)	1.50(1.30)	20,30	D
AWVT002520103R3□00	3.3	1MHz,200mV	0.220	1.10(1.00)	1.20(1.00)	20,30	E
AWVT002520106R8□00	6.8	1MHz,200mV	0.435	0.78(0.70)	0.84(0.75)	20,30	G


Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

1. Operating temperature range $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current.
3. I rms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:
 L: HP4285A+HP42841A
 RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent
 Isat: Agilent HP4284A
 I rms: Agilent HP4284A


AWVT00252010 Type

Characteristics Graph


Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

AWVT00252012 Type
■ Dimensions


unit:mm

■ Recommended Land Pattern


unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT00252012R47□00	0.47	1MHz,200mV	0.027	3.70(3.30)	3.10(2.70)	20,30	A

Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

1. Operating temperature range -40°C ~ 125°C (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current.
3. Irms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:

L: HP4285A+HP42841A

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent


Isat: Agilent HP4284A

Irms: Agilent HP4284A


AWVT00252012 Type

■ Characteristics Graph


Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

AWVT00303010 Type
■ Dimensions


unit:mm

■ Recommended Land Pattern


unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT003030101R0□00	1.0	1MHz,200mV	0.063	2.40(2.10)	2.30(2.00)	20,30	1R0
AWVT003030103R3□00	3.3	1MHz,200mV	0.165	1.20(1.00)	1.10(0.99)	20,30	3R3

Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

- Operating temperature range $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current.
- Irms for a 40°C temperature rise from 25°C ambient with current
- Measure Equipment:

L: HP4285A+HP42841A

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent


Isat: Agilent HP4284A

Irms: Agilent HP4284A


AWVT00303010 Type

Characteristics Graph


Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

AWVT00303012 Type
■ Dimensions


unit:mm

■ Recommended Land Pattern


unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT00303012R47□00	0.47	1MHz,200mV	0.032	4.3(3.87)	4.0(3.60)	20,30	R47
AWVT003030121R0□00	1	1MHz,200mV	0.06	3.1(2.79)	3.0(2.70)	20,30	1R0
AWVT003030121R5□00	1.5	1MHz,200mV	0.072	2.7(2.43)	2.6(2.34)	20,30	1R5


Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

- Operating temperature range -40°C ~ 125°C (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current.
- Irms for a 40°C temperature rise from 25°C ambient with current
- Measure Equipment:
 L: HP4285A+HP42841A
 RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent
 Isat: Agilent HP4284A
 Irms: Agilent HP4284A


AWVT00303012 Type

■ Characteristics Graph



Inductance vs. DC Current



Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

AWVT00404012 Type
■ Dimensions

■ Recommended Land Pattern

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT00404012R50□00	0.5	1MHz,200mV	0.030	3.90(3.50)	3.5(3.10)	20,30	R50
AWVT004040121R0□00	1.0	1MHz,200mV	0.040	2.90(2.60)	3.0(2.70)	20,30	1R0
AWVT004040121R5□00	1.5	1MHz,200mV	0.051	2.30(2.00)	2.5(2.20)	20,30	1R5
AWVT004040122R2□00	2.2	1MHz,200mV	0.060	1.90(1.70)	2.3(2.00)	20,30	2R2
AWVT004040124R7□00	4.7	1MHz,200mV	0.094	1.30(1.10)	1.8(1.60)	20,30	4R7
AWVT004040126R8□00	6.8	1MHz,200mV	0.135	1.00(0.95)	1.5(1.30)	20,30	6R8
AWVT00404012150□00	15	1MHz,200mV	0.260	0.78(0.70)	1.0(0.90)	20,30	150
AWVT00404012220□00	22	1MHz,200mV	0.390	0.62(0.55)	0.8(0.72)	20,30	220

Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

1. Operating temperature range -40°C ~ 125°C (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current
3. I rms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:

L: HP4285A+HP42841A

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent


Isat: Agilent HP4284A

I rms: Agilent HP4284A


AWVT00404012 Type

Characteristics Graph


Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

AWVT00404015 Type
■ Dimensions


unit:mm

■ Recommended Land Pattern


unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT004040151R0□00	1.0	1MHz,200mV	0.034	3.6(3.20)	3.7(3.30)	20,30	1R0
AWVT004040153R3□00	3.3	1MHz,200mV	0.080	2.0(1.80)	2.2(1.90)	20,30	3R3


Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

1. Operating temperature range $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current
3. I rms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:
 L: HP4285A+HP42841A
 RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent
 Isat: Agilent HP4284A
 I rms: Agilent HP4284A


AWVT00404015 Type

Characteristics Graph

Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.


AWVT00404026 Type

Dimensions



unit:mm

Recommended Land Pattern



unit:mm

Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω) \pm 30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (\pm %)	Marking
AWVT00404026R47□00	0.47	100kHz,1V	0.024	7.20(6.4)	4.80(4.3)	20,30	R47
AWVT00404026R50□00	0.50	100kHz,1V	0.024	7.20(6.4)	4.80(4.3)	20,30	R50

Note: When ordering, please specify tolerance code. Tolerance: M= \pm 20% / T= \pm 30%

1. Operating temperature range $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current
3. I rms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:

L: HP4285A+HP42841A

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent


Isat: Agilent HP4284A

I rms: Agilent HP4284A


AWVT00404026 Type

■ Characteristics Graph


Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

AWVT00505020 Type
■ Dimensions


unit:mm

■ Recommended Land Pattern


unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT00505020R47□00	0.47	100kHz,1V	0.0135	8.0(7.2)	5.5(5.0)	20,30	R47
AWVT005050203R3□00	3.3	100kHz,1V	0.050	3.4(3.00)	2.7(2.40)	20,30	3R3

Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

1. Operating temperature range -40°C ~ 125°C (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current
3. I rms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:

L: HP4285A+HP42841A

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent


Isat: Agilent HP4284A

I rms: Agilent HP4284A


AWVT00505020 Type


Characteristics Graph

Inductance vs. DC Current




Temperature Change vs. DC Current



AWVT00606020 Type
■ Dimensions


unit:mm

■ Recommended Land Pattern


unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVT006060201R0□00	1.0	100kHz,1V	0.019	6.4(5.70)	4.2(3.70)	20,30	1R0
AWVT006060201R5□00	1.5	100kHz,1V	0.026	5.4(4.80)	3.7(3.30)	20,30	1R5
AWVT006060202R2□00	2.2	100kHz,1V	0.034	4.5(4.00)	3.3(2.90)	20,30	2R2
AWVT006060203R3□00	3.3	100kHz,1V	0.045	3.6(3.20)	2.8(2.50)	20,30	3R3
AWVT006060206R8□00	6.8	100kHz,1V	0.085	2.6(2.30)	1.9(1.70)	20,30	6R8


Note: When ordering, please specify tolerance code. Tolerance: M=±20% / T=±30%

- Operating temperature range $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (Including self - temperature rise)
- Isat for Inductance drop 30% from its value without current
- Irms for a 40°C temperature rise from 25°C ambient with current
- Measure Equipment:
 - L: HP4285A+HP42841A
 - RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent
 - Isat: Agilent HP4284A
 - Irms: Agilent HP4284A


AWVT00606020 Type

Characteristics Graph

Inductance vs. DC Current




Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.


AWVT00808040 Type

■ Dimensions



unit:mm

■ Recommended Land Pattern



unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	RDC (Ω) $\pm 30\%$	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance ($\pm\%$)	Marking
AWVT008080401R0□00	1.0	100kHz,1V	0.0075	13.5(12.00)	8.1(7.10)	20,30	1R0
AWVT008080401R5□00	1.5	100kHz,1V	0.0097	10.5(9.30)	7.7(6.80)	20,30	1R5
AWVT008080402R2□00	2.2	100kHz,1V	0.0120	9.7(8.60)	7.2(6.30)	20,30	2R2
AWVT008080403R3□00	3.3	100kHz,1V	0.0170	8.0(7.10)	5.9(5.20)	20,30	3R3
AWVT008080406R8□00	6.8	100kHz,1V	0.0290	5.8(5.10)	4.9(4.30)	20,30	6R8

Note: When ordering, please specify tolerance code. Tolerance: M= $\pm 20\%$ / T= $\pm 30\%$

1. Operating temperature range $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (Including self - temperature rise)
2. Isat for Inductance drop 30% from its value without current
3. I rms for a 40°C temperature rise from 25°C ambient with current
4. Measure Equipment:

L: HP4285A+HP42841A

RDC: DIGITAL MILLINHM METER CHROMA 16502, or equivalent


Isat: Agilent HP4284A

I rms: Agilent HP4284A


AWVT00808040 Type

Characteristics Graph

Inductance vs. DC Current





Temperature Change vs. DC Current



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

■ Packaging


Tape Dimensions



Reel Dimensions

Figure 1

Figure 2



Dimensions in mm

TYPE	Fig	Tape Dimensions										Reel Dimensions					Quantity PCS / Reel
		A0	B0	K0	D	E	F	W	P	P0	P2	A	B	C	D	E	
AWVT00201610	1	1.9	2.2	1.15	1.55	1.75	3.5	8	4	4	2	180	60	13	14.4	8.4	2000
AWVT00252010	1	2.4	2.7	1.15	1.55	1.75	3.5	8	4	4	2	180	60	13	14.4	8.4	2000
AWVT00252012	1	2.40	2.70	1.35	1.55	1.75	3.5	8	4	4	2	180	60	13	14.4	8.4	2000
AWVT00303010	1	3.2	3.2	1.4	1.55	1.75	3.5	8	4	4	2	180	60	13	14.4	8.4	2000
AWVT00303012	1	3.2	3.2	1.4	1.55	1.75	3.5	8	4	4	2	180	60	13	14.4	8.4	2000
AWVT00404012	2	4.25	4.25	1.3	1.55	1.75	5.5	12	8	4	2	178	60	13	13.2	-	1000
AWVT00404015	2	4.25	4.25	1.7	1.55	1.75	5.5	12	8	4	2	178	60	13	13.2	-	1000
AWVT00404026	2	4.25	4.25	3	1.55	1.75	5.5	12	8	4	2	178	60	13	13.2	-	500
AWVT00505020	2	5.25	5.25	2.2	1.55	1.75	5.5	12	8	4	2	330	100	13	13.4	-	2000
AWVT00606020	2	6.25	6.25	2.2	1.55	1.75	5.5	12	8	4	2	330	100	13	13.4	-	2000
AWVT00808040	2	8.25	8.25	4.15	1.55	1.75	7.5	16	12	4	2	330	100	13	17.4	-	1000

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.