Current Compensated Noise Suppression Chokes

FE 3X Series - 3 Phase Common Mode Choke









- © Complies with VDE 565-2
- UL recognized (94V0)
- Rated voltage: 500Vac Rated current: 6 to 16A
- 2Withstanding voltage: 2500Vac @ 2 sec


Electrical Specifications @ 25°C - Operating Temperature -40°C to +125°C							
Part Number	I (A) (40°C)	L (mH) (+40%, -30%)	Rdc (mΩ) (+/- 10%)	Fo (kHz) (MIN)	Attentuation (dB at F0)	Pins Ø (mm)	Height MAX (mm)
FE3X050-10-7NL	6	5	25	200	48	1.10	35
FE3X033-10-7NL	8	3.1	14	200	41	1.30	35
FE3X025-10-7NL	16	2.2	6.3	400	31	1.8	47

Notes: The "NL" suffix indicates an RoHS-compliant part number. **Non-NL** suffixed parts are not necessarily RoHS compliant, but are electrically and mechanically equivalent to the **NL** versions.

Mechanicals Schematics







For More Information

Americas - prodinfo_power_americas@yageo.com | Europe - prodinfo_power_emea@yageo.com | Asia - prodinfo_power_asia@yageo.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. Pulse Electronics, Inc. All rights reserved.

YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.

PulseElectronics.com P539.C (01/24)